

Marktek Inc.
Your One-Stop Shop for Conductive, Resistive, & Microwave-Absorptive Materials

Data Sheet for TCS72T

ID Number:	TCS72T
Part Number:	PF4523PW
Description:	Nylon taffeta fabric coated with tin over copper over silver
Thickness, mils:	3 (76 um)
Basis Weight, oz/yd ²	2.1 (72 g/m ²)
Width, in (nominal)	52 (132 cm)
Surface Resistivity, ohm/sq	<0.02
Shielding Effectiveness @ 1 GHz, db	90
Metal Adhesion*:	Pass, no metal loss
Abrasion Resistance, cycles:	1,000,000
Cold Exposure*:	No cracking
Salt Fog Resistance*:	NA
Temperature Range, °C:	-30 to 190 (short-term)
Avg. Roll Length, yd.:	220 (200 m)

*Metal adhesion, ASTM D3359; salt fog test, ASTM B117; cold exposure test samples chilled to -45°C, then flexed 180° around a 1/8" diameter rod while at -45°C.

The information provided here is for illustrative purposes only and should not be considered a product specification. As always, it is up to the user of this product to make the final determination as to whether the said product is suitable for the user's intended application.

13621 Riverway Dr.
Suite H
Chesterfield, MO 63017

Tel: 314-878-9190
Fax: 314-878-9558
Email: info@marktek-inc.com

www.Marktek-Inc.com

