

## Marktek Inc.

Your One-Stop Shop for EMI-shielding, Conductive, Resistive, & Microwave-Absorptive Materials

### Data Sheet for S400MY Conductive Yarn

**Description:** silver-plated nylon 66, 1400 dtex, round monofilament yarn

**Appearance:** silvery gray

**Finished dtex:** 1500±10

**Nominal Diameter:** 400 um (16 mils)

**Linear Resistance:** < 60 ohm/cm (150 ohm/in)

**Yield:** 3,333 yd/lb (6,667 m/kg) ±6%

**Tenacity:** ≤ 60 cN/tex

**Breaking Strength:** NA

**Elongation at Break:** 30±5%

**Temperature Limits:** up to 100°C

**Packaging:** 400±40 g (net) spools on paper or plastic, 230 mm, 3°-30 cones; 15 or 30 per case

**Applications:** Conductive thread or wire for ESD, medical, EMI knitted gasket, and smart textiles applications. Silver is a broad spectrum biocide, so the product can be used wherever antimicrobial properties are desired.

The information provided here is for illustrative purposes only and should not be considered a product specification. All statements and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. As always, it is up to the user of this product to make the final determination as to whether the said product is suitable for the user's intended application.

Rev. 06/19

13621 Riverway Dr.  
Suite H  
Chesterfield, MO 63017

Tel: 314-878-9190  
Fax: 314-878-9558  
Email: [info@marktek-inc.com](mailto:info@marktek-inc.com)

[www.Marktek-Inc.com](http://www.Marktek-Inc.com)