

Marktek Inc.
Your One-Stop Shop for Conductive, Resistive, & Microwave-Absorptive Materials

Data Sheet for TCPB15

ID Number:	TCPB15
Description:	Nylon pattern-bonded nonwoven coated with tin over copper over flash Ag plus anti-tarnish coating
Thickness, mils:	12 (0.30 mm) \pm 20%
Basis Weight, oz/yd ² :	3.1 (105 g/m ²) \pm 20%
Width, in (nominal):	39.4 (100 cm) \pm 1"
Surface Resistivity, ohm/sq:	<0.02
Avg. Shielding Effectiveness from 30 MHz to 1 GHz, db:	90
Metal Adhesion*:	Pass, no metal loss
Abrasion Resistance, cycles:	NA
Cold Exposure*:	No cracking
Salt Fog Resistance*:	NA
Temperature Range, °C:	-30 to 100
Avg. Master Roll Length, yd.:	220 (200 m), 1 splice/100 m

*Metal adhesion, ASTM D3359; salt fog test, ASTM B117; cold exposure test samples chilled to -45°C, then flexed 180° around a 1/8" diameter rod while at -45°C.

The information provided here is for illustrative purposes only and should not be considered a product specification. As always, it is up to the user of this product to make the final determination as to whether the said product is suitable for the user's intended application.

rev. 0119

13621 Riverway Dr.
Suite H
Chesterfield, MO 63017

Tel: 314-878-9190
Fax: 314-878-9558
Email: info@marktek-inc.com

www.Marktek-Inc.com